

# 2008 Super Chief I - Ambulance - Braun Industries, Inc.

## SUMMARY SPECIFICATIONS 2008 INTERNATIONAL LP4300

Overall Length	291.5"	Curb Weight*	14,690 lb.
Overall Width	96.0	Front Payload Available*	TBD
Overall Height	112.0	Rear Payload Available*	TBD
Module Length	170.0	Combined (Total) Payload	5,310 lb.
Module Interior Height	73.0	G.V.W.R.	20,000 lb.
Module Floor Height	32.0	*Based on Select Package	

Select    Prestige

### CHASSIS - OEM

AIR CONDITIONING - OEM high output fresh air heater & air conditioner system	X	X
AIR SUSPENSION - 12,000 lbs. Rated air suspension with rear door load dump feature	X	X
ALTERNATOR - 270 AMP Leece Neville alternator system	X	X
BRAKES - Hydraulic disc with four channel ABS	X	X
BRAKE-PARKING - Air-Operated with "push/pull" dash mounted knob	X	X
BUMPER, FRONT - Chrome plate steel	X	X
CHASSIS - 2008 International LP 4300 - 175" Wheelbase	X	X
CRUISE CONTROL -	X	X
ENGINE - International DT466 220HP with block heater	X	X
FRONT AXLE RATING - 8,000 lbs. (8,000 lbs. G.A.W.R.)	X	X
FRONT SPRING RATING - 8,000 lbs	X	X
FUEL TANK - Single fuel tank - 50 gallons	X	X
G.V.W.R. - 20,000 lbs.	X	X
GAUGES, CHASSIS - Temperature, oil pressure, fuel, voltmeter, tach	X	X
HORNS - Dual tone electric horns & Grover Air w/single frame mounted trumpet	X	X
LIGHT, DOME - Dome light with dual adjustable lights	X	X
MIRROR, INTERIOR CAB - Cab interior day/night cab mirror	X	X
POWER WINDOWS AND LOCKS -	X	X
RADIO - Panasonic w/ Cassette	X	X
REAR AXLE RATING - 15,500 lbs (12,000 lbs G.A.W.R.), 4.10 Rear axle ratio	X	X
REAR SPRING RATING - 15,500 lbs	X	X
SEATS - National high back air suspension	X	X
SHOCK ABSORBERS - Heavy duty shock absorbers on front and rear	X	X
STEERING - Tilt steering wheel	X	X
TIRE, SPARE - Spare tire - steering - shipped loose	X	X
TIRES - (6) 245/70R x 19.5F steel belted radial, all-season tires	X	X
TRANSMISSION - Allison 2100 series 5-speed automatic	X	X
TRIM PACKAGE - OEM STD Interior and exterior package	X	X
WIPERS - Intermittent 2- speed windshield wipers with washer	X	X

**CHASSIS CONVERSION**

AIR RIDE DUMP SWITCH – to disable air ride dump	X	X
AUXILARY CONDENSER – Shall be added to OEM air conditioning system	X	X
BATTERY SYSTEM - Triple battery system rated at 1950 CCA under driver's side step	X	X
FLOOR CONSOLE - ABS floor mounted console with recessed storage, drink, & map holder		X
FUEL - The fuel tank(s) shall be full at time of delivery	X	X
HEAT SHIELDS - Above muffler and exhaust system	X	X
MIRROR, EXTERIOR - Exterior OEM – Heated/Remote- bright finish w/ LED clearance light	X	X
RUNNING BOARDS - NFPA anodized aluminum diamond plate tank and step covers	X	X
VALVE EXTENSIONS - Air Max AML 1 valve extensions	X	X
WHEEL SIMULATORS - Stainless steel wheel simulators	X	X

**ELECTRICAL SYSTEMS FEATURES**

ALARM, BACKUP -	X	X
ATTENDANT CONTROL PANEL (ACP) -	X	X
CONVERTER / BATTERY CONDITIONER - 45 amp	X	X
ELECTRICAL CIRCUITS - High temperature "SXL" wiring for 12 volt ambulance circuits, high temperature thermoplastic loom on all harnesses, SGX battery/charging system cables	X	X
GFCI - 20 amp GFCI circuit breaker	X	X
INVERTER PREWIRE - Pre-wired for inverter installation, terminated behind the passenger's seat	X	X
LIGHT, ACP (ATTENDANT CONTROL PANEL) - Light over ACP	X	X
LIGHT, CLEARANCE - ICC - ICC body lights are LED with chrome trim	X	X
LIGHT, DOME - (10) Dual intensity dome lights with 3-way hi & low switching	X	X
LIGHT, DOOR OPEN INDICATOR - Separate "door open" warning lights for entrance & OSS doors	X	X
LIGHT, FLUORESCENT - (5) 12 vdc powered fluorescent lights in the patient compartment	X	X
LIGHT, OUTSIDE STORAGE (OSS) - Each OSS compartment automatically illuminated	X	X
LIGHT, PDQ - Automatic light in PDQ	X	X
LIGHT, SPOT HAND-HELD - "Blue-eye" 400,000 candle power hand-held spotlight	X	X
LOCKS, POWER DOOR - Electric doors for OSS and people doors with keyless entry remote		X
ELECTRICAL SYSTEM - Weldon V-Mux Microprocessor based, multiplex system with Vista III color monitor	X	X
MCC (MASTER CONTROL CONSOLE) -	X	X
METER, HOUR - Engine hour meter	X	X
OUTLET, INTERIOR 125 VAC - (3) 125 vac lighted patient compartment outlets	X	X
OUTLET, INTERIOR 12VDC - (2) 12 vdc outlets (power point) with Schottky diode isolator	X	X
PATIENT STATUS COMMUNICATION - Push button communication to alert driver's Vista III display	X	X
PDQ (POWER DISTRIBUTION QUARTERS) - Weldon V-Mux digital electronic control system	X	X
RADIO ANTENNA BASE - (2) Antenna bases	X	X
RECEPTACLE, SHORELINE - 20 amp Kussmaul Super auto eject inlet receptacle with circuit interrupt	X	X
SWITCH, BLOCK HEATER - Block heater connected to shoreline with summer/winter switch in PDQ	X	X
REAR VISION CAMERA – Audiovox rear vision camera on module rear connected to cab Vista display		X
SWITCH, EMERGENCY MASTER -	X	X
SWITCH, MCC AND ACP - Weldon V-Mux digital display with touch pad switches	X	X
SWITCH, MODULE POWER - With adjustable timer	X	X

**EMERGENCY WARNING EQUIPMENT**

LIGHT BAR, FRONT - Whelen 45FH Module Mounted – (2) Red & (1) Clear halogen flashers , & (4) red rotators	X	
LIGHT BAR, FRONT – Whelen 45FL Module Mounted – (8) 700 red and (1) clear center LED flashers		X
LIGHT BAR, REAR - Whelen 45RH - (4) red rotators, (2) red, (1) amber halogen flashers, and (2) scenes	X	
LIGHT BAR, REAR - Whelen 45RL (6) red, (1) amber 700 LED flashers, and (2) scenes	X	
LIGHT, FLASHING HEADLIGHTS - with daytime running lights		X
LIGHT, GRILLE - (2) Whelen 700 Series red halogen grill lights in aluminum housings	X	
LIGHT, GRILLE - (2) Whelen 700 Series red Super LED grille lights in aluminum housings		X
LIGHT, INTERSECTION - (2) Whelen 700 Series red halogen intersection lights in 15° tilt housings	X	
LIGHT, INTERSECTION - (2) Whelen 700 Series red Super LED intersection lights in 15° tilt housings		X
LIGHT, MODULE FRONT - (2) Whelen 900 red and (1) Whelen 700 center clear halogens with chrome bezels	X	
LIGHT, MODULE FRONT - (2) Whelen 900 Super red and (1) Whelen 700 white center LEDs with chrome bezels		X
LIGHT, MODULE SIDE - (4) Whelen 900 Series red and (4) Whelen 900 Series clear halogen scenes with bezels	X	
LIGHT, MODULE SIDE – (4) Whelen 900 Series Super red LED and (4) Whelen 900 Series clear halogen scenes with bezels		X
LIGHT, REAR INTERSECTION - (2) Whelen 700 Series red Super LED wheel well lights with chrome bezels		X
LIGHT, REAR WINDOW LEVEL - (2) Whelen 900 Series red Super LED with chrome bezels		X
LIGHT, STOP REAR - Rear centered high mount LED stop light in rear light bar	X	X
LIGHT, TAIL - Whelen 600 series incandescent brake / tail / Turn, and halogen back-up lights in chrome bezels	X	
LIGHT, TAIL - Whelen 600 series LED brake / tail /turn and halogen back-up lights with chrome bezels		X
PARK OVERRIDE -	X	X
SIREN - Whelen 295FHS/A7 dual amp remote with microphone	X	X
SPEAKERS, SIREN - Dual CPI through the bumper 100 watt siren speakers	X	X

**MODULE FEATURES**

ANTI-CORROSION PACKAGE - Nylon screw-hole inserts, nylon hinge strips, ceramic hinge bolts, & ECK spray	X	X
ASSIST HANDLES - (3) "V" stainless steel assist handles and (3) black urethane coated	X	
ASSIST HANDLES - (2) "V" stainless steel assist handles and (4) black urethane coated		X
BATTERY STORAGE - Under Driver's side step	X	X
BODY CONSTRUCTION - SolidBody construction of welded .125" thick minimum 5052-H32 aluminum	X	X
COMPARTMENT, EXTERIOR #1 - (2) Adjustable shelves	X	X
COMPARTMENT, EXTERIOR #2 - (1) Adjustable shelf	X	X
COMPARTMENT, EXTERIOR #3 - Inside/Outside access, (2) adjustable shelves	X	X
COMPARTMENT, EXTERIOR #4 - 4A - Storage for backboards/scoop stretchers, 4B – Oxygen tank storage	X	X
COMPARTMENT, EXTERIOR #5 - Inside/Outside access, (2) adjustable shelves	X	X
COMPARTMENT, SWEEP-OUT DESIGN - Compartments # 1,2,3, & 4	X	
CONNECTIONS, MODULE - Secured with (10) 12mm bolts through rubber spacers	X	X
DOOR, SLIDING CURBSIDE PASSAGE -		X
DOOR, CONSTRUCTION – Inverted pan design of .190" thick aluminum with the gasket on the doors	X	X
DOOR HANDLES, Chrome Eberhart free-floating design with rotary locks	X	X
FENDERETTES - Anodized polished aluminum module fenderettes	X	X
INSULATION - Nominal 3/4" thick Class 1 fire retardant sprayed urethane insulation	X	X
MATTING, CURBSIDE DOORWAY - Entrance shall have skid resistant gray turtle tile	X	X
MUD FLAPS, REAR -	X	X
PAINT, MODULE - PPG Delta low voc polyurethane with buffed clear coat to match cab	X	X
RUB RAILS - Anodized polished aluminum rub rails with 5/8" wide black reflective scotchlite	X	X
SCOTCHLITE - 60 sq. inch reflective panel installed on all hinged passage doors	X	X

**MODULE FEATURES (Cont.)**

STAINLESS STEEL PANELS - On the lower interior portion of each passage door	X	X
STEP REAR FLIP-UP BUMPER – Aluminum grip strut material with hinged center flip-up section	X	X
STONE GUARDS - Front anodized 24" high aluminum diamond plate	X	X
THRESHOLD, SIDES – Stainless steel covering on all exterior compartment lower door jambs	X	X
THRESHOLD, REAR - Anodized aluminum diamond plate rear threshold	X	X
TOW LOOPS, REAR - (2) tow hooks in rear step area	X	X
WINDOW, PASSAGE DOORS - (2) fixed rear & (1) openable side with tint	X	X

**PATIENT COMPARTMENT FEATURES**

SQUAD BENCH NET – Attached at forward end of squad bench	X	X
ASPIRATOR SYSTEM - Recessed Impact 324 self-contained system	X	X
ATTENDANT /CHILE SEAT - Combination adult/child attendant seat on sliding swivel base		X
ATTENDANT SEAT & BASE - High back, attendant seat mounted on sliding swivel base	X	
CABINET BEHIND ATTENDANT SEAT - (1) Compartment with slide-out tray for (3) "D" cylinders		X
CABINET BEHIND ATTENDANT SEAT - (1) Compartment	X	
CABINET DOORS - 1/4" thick light bronze acrylic sliding doors with inventory control tag handles	X	X
CABINET FACE - High pressure high gloss plastic laminate	X	X
CABINET, LOWER FRONT WALL - (1) Compartment with inside/outside access and (2) shelves	X	X
CABINET, STREETSIDE ALS - (5) Compartments with (3) restocking frames and Corian counter tops		X
CABINET, STREETSIDE ALS - (4) Compartments with laminated counter tops	X	
CABINET, UPPER FRONT WALL - (2) compartments with locking drug storage		X
CABINET, UPPER FRONT WALL - (2) Compartments	X	
CLOCK - LaCrosse Technology 10" diameter, 12/24 hour battery operated Atomic Clock	X	X
COT FASTENER - Ferno Washington #175-4 two-position, - side and center- for model 35 cot	X	X
DRAWER, SLIDEOUT WITH TABLE - with hinged plexi writing table, streetside wall by attendant seat	X	X
FLOOR COVERING - Loncoin II single piece flooring, coved streetside and curbside	X	
FLOOR COVERING – Lon-Plate II single piece flooring upgrade, coved streetside and curbside		X
FLOOR CONSTRUCTION - ¾" composite material (Non-wood) over .125" Aluminum	X	X
GLOVE DISPENSER, THREE BOX - (3) glovebox holder mounted above side entry door		X
GRAB RAIL - 96" L stainless steel ceiling grab rail installed above the cot area	X	X
GRAB RAIL, SQUAD BENCH - 64" L stainless steel ceiling grab rail installed above squad bench		X
HEADLINER - White vinyl clad aluminum patient compartment headliner	X	X
HEATER / AIR CONDITIONER SYSTEM - High capacity 475 CFM fresh air heavy duty heater/air conditioner	X	X
I.V. HANGERS - (2) recessed dual ceiling I.V. hangers	X	X
OXYGEN CYLINDER STORAGE - Storage for (1) "M" or "H" size oxygen cylinder	X	X
OXYGEN SYSTEM ELECTRIC - Switch, monitor, by-pass (3) Ohio Med outlets, regulator, & flow meter	X	X
PARTITION DOORWAY & DOOR - Hinged partition door with window	X	X
RADIO SPEAKERS - (2) Stereo speakers in rear head pad with fader control in radio	X	X
SHARPS & TRASH CONTAINERS - Built into forward end of squad bench with spring loaded plexi lid	X	X
SIGNS - (2) No smoking, oxygen equipped, fasten seat belt signs	X	X
SQUAD BENCH BASE - sprayed with sound absorbing polyurethane material	X	X
SQUAD BENCH CUSHION - with auto-latch and hold-open gas cylinders	X	X
STAINLESS STEEL WALL PROTECTION - Stainless steel wall panels on streetside from CPR seat down	X	X
UPHOLSTERY - Heavy duty expanded vinyl	X	X
VENTILATOR, EXHAUST - Three - Speed		X
WALL COVERING, ACCENT STRIPE - Color coordinated laminated inset stripe at streetside counter area		X
WALL COVERINGS - High pressure high gloss plastic laminate	X	X
WINDOW, CURBSIDE - 12" x 32" window with dry-erase board used as a sliding cover		X

**KKK-A-1822F**

---

KKK-A-1822F COMPLIANT

X

X