

MERET



MERET OXYGEN REGULATORS

MERET oxygen regulators incorporate the latest in technology to deliver the highest level of safety, reliability, durability, and precision flow. EMS series unibody regulators are constructed from high strength solid brass with brass internal high pressure flow components to ensure added strength and safe operation.

MERET

877.222.0200
www.MeretUSA.com
info@meretusa.com
Ph: 714.259.4700
Fx: 714.259.4749



MAGNUM SERIES ALL-BRASS OXYGEN REGULATOR



Rubberized Comfort Grip Handknob

Brass/Viton Regulator-Cylinder Washer Seal

Solid Stainless Steel Index Pins

Metal Gauge Protector

Durable Chrome Plated Finish

12 Position Flow +/- 10%

Sintered 40 Micron Triple Inlet Filter

Low Profile Impact Resistant Pressure/Contents Gauge

Optional DISS Power Take-offs with Check Valves

Serialized Regulator Identification

Durable Universal Barbed Outlet

Durable Aluminum Flow Control Knob



Barb Only

Barb and 1 PTO

Barb and 2 PTO



Product Dimensions:
6.5" x 3.5" x 3.5"
Product Weight:
2 lbs 1 oz

BRUIT



- All brass unibody, metal flow knob
- 0-2 PTO and barb

ECONOMY



- Aluminum outer body
- Multiple flow options + PTO

MINI



- Smallest O2 reg at only 4.0" in length, 0.7 LB + PTO

FLOWMETER



- Compact, lightweight
- Uses 1/8" Male NPT connection

PRESSURE REDUCER



- All brass, compact
- 2 PTO w/ check valves

OMNIVALVE



- Valve integrated regulator
- All brass, 1 PTO + barb

MERET CGA REGULATOR OPTIONS					
REGULATOR	MODEL	FLOWS (L/MIN)	50 PSI POWER TAKE-OFFS (PTO)	CONSTRUCTION	WARRANTY LIFETIME
MAGNUM	EMS/MREG8725-xxx	0-25	2 + Barb	Solid 360 Brass, Chrome Plated	5 yr
BRUIT	EMSREG8725-xxx	0-25	0-2 + Barb	Solid 360 Brass, Chrome Plated	5 yr
ECONOMY	AREG87xx-xxx	0-4, 0-8, 0-15, 0-25	0, 2 + Barb	Aluminum/ Brass Internal, Anodized	5 yr
MINI	AREG87xxME-BU	0-8, 0-15	Barb Only	Aluminum/ Brass Internal, Anodized	5 yr
FLOWMETER	MFMC-25	0-25	N/A	Aluminum/ Brass Internal, Anodized	5 yr
PRESSURE REDUCER	PRREG64-2D	50 PSI Preset	2	Solid 360 Brass, Chrome Plated	5 yr
OMNIVALVE	AIO-3-xx	0-8, 0-5, 0-25, integral valve	1 + Barb	Solid 360 Brass, Chrome Plated	5 yr

All regulators are individually calibrated and tested 100% for flow and leak. ASTM G175, ISO 13085, ISO 9001:2000