POWER X2™



Raise expectations.

The new FERNO® POWER X2™ Ambulance Cot is cross-compatible and offers more power, visibility, and maneuverability than today's leading competitive powered cots. Designed, engineered, and built for safety and ease of use under challenging circumstances. It brings stability to unpredictable environments for operators, allowing them to focus on safe patient care and transportation.

*CROSS**LOCK***

UNIVERSALLY COMPATIBLE
WITH MANUAL AND POWERED
FASTENING SYSTEMS

*EZ**GLIDE***

27% LARGER WHEELS
INCREASED GROUND CLEARANCE
ENHANCED STABILITY
GREATER MANEUVERABILITY

*SCENE**BRIGHT***

360° ILLUMINATION
TWO-STAGE LIGHTING

*ENDURA**CHARGE***

36-VOLT LiFePO4 BATTERY
LASTS 2X LONGER THAN COMPETITOR'S

FERNO®

POWER X2™

ENHANCED PATIENT CARE, COMFORT, AND SAFETY

- Adjustable pneumatic backrest enhancing patient comfort
- Sealed bolstered mattress for increased patient comfort (features a sanitary hook and loop style design)
- Shock frame raises patient's feet for treatment of shock
- Knee gatch* increases clearance between foot-end operator and patient's feet for added comfort
- Customize with a variety of accessories to meet patient needs

INCREASED PARAMEDIC SAFETY, EFFICIENCY, AND MANEUVERABILITY

- 8" **EZGlide** wheels, increase ground clearance and provide superior performance
- Increased illumination with our **SceneBright** technology, a two-stage LED lighting that provides 360° illumination
- Increased maneuverability in tight spaces with our telescoping load frame
- Directional wheel locks* for additional control in tight areas
- Push pull bar* for optimal control and comfort when transporting patients at lower heights
- Programmable load height to match your ambulance floor
- Manual operation option in the event of power loss
- Backrest-mounted equipment hook helps keep hands free

SUSTAINABLE INVESTMENT WITH CROSS-COMPATIBLE DESIGN

- The FERNO® POWER X2™ is compatible with:
  - FERNO POWER F2™ fastening system**
  - FERNO PRO F1 manual fastener**
  - FERNO and Stryker® Antler Rail systems / mass casualty fasteners
  - Stryker Performance-LOAD® manual fastener**
  - Stryker Power-LOAD® loading system**

ENGINEERED FOR RELIABILITY, DURABILITY, AND PERFORMANCE

- Hose-free actuator design for greater reliability and weight reduction
- ICS® Integrated Charging System improves battery management** (available with Power F2 and Pro F1 Universal Cot Fastener)
- LCD screen displays cot cycle count for maintenance planning
- Controlled environment testing to 10+ years of service

* OPTIONAL EQUIPMENT

** COMPATIBILITY KIT NEEDED TO SECURE THE FERNO® POWER X2™ INTO THE FERNO® POWER F2™, FERNO® PRO F1, STRYKER® PERFORMANCE-LOAD® AND STRYKER® POWER-LOAD®.

SPECIFICATIONS

ITEM NUMBER
0015816

LENGTH (MAX)
79.7" / 2024.5 MM

LENGTH (MIN)
65.5" / 1663 MM

WEIGHT*
146 LB / 66 KG

LOAD CAPACITY
700 LB / 318 KG (UNASSISTED)
1,100 LB / 498 KG (IN RETRACTED POSITION)

POWER
36.3 VOLT LiFePO4

*WEIGHT WITHOUT MATTRESS AND RESTRAINTS.

FERNO® RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.

ACCESSORIES

PUSH PULL LIFT BAR
IV POLE
STO NET
PAC RAC
POLE MOUNTS
LOAD FRAME O2 HOLDER
BACKREST O2 HOLDER
BACKREST POUCH
PEDI MATE® +
NEO MATE
KANGOOFIX
LBS JR.

STANDARD EQUIPMENT

EQUIPMENT HOOK
BOLSTERED MATTRESS
FOOT-END WHEEL LOCKS
FOOT-END LEAD HANDLE
ANTLER AND RAIL COMPATIBILITY
SCENE LIGHTS
COLOR CODED X-RESTRAINTS
STATUS DISPLAY WITH CYCLE COUNTER
36V LiFePO4 BATTERY

COMPLIANCE*

SAE J3027
CAAS-GVS
IP56
KKK-A-1822F
NFPA 1900
IEC 60601-1-2
ISTA 3B
EN 1789 (IN PROCESS)

*THE FERNO® POWER X2™ IS COMPLIANT WITH THE ABOVE STANDARDS WHEN USED WITH THE PRO F1™ COMPATIBILITY KIT.

FERNO®

Penn Care
Many Needs ... One Solution

www.penncare.net
sales@penncare.net
1-800-392-7233